



PRICE SHEET

**POWER VENTED
LOW STATIC, AXIAL FAN,
UNIT HEATER**

PLAN
List Price Form RZ-NA \$-UDAP
EFFECTIVE MARCH 1, 2002


APPLIES TO MODEL UDAP

SHIPMENT, TITLE AND RISK OF LOSS

All prices quoted are FOB destination. Title to and risk of loss for all products will remain with Thomas & Betts until product is delivered by the common carrier. Prices apply to continental U.S.A. and Canada (payable in U.S. funds).




NOTE: The manufacturer reserves the right to add components (at net prices) when necessary to obtain the operation desired by the customer.

KEY: Base price includes all items listed as standard (STD); - indicates no change in price; ■ indicates not available.



Model UDAP, Power Vented Low Static Unit Heater

- Sizes 30-125 certified for residential heating application
- Sizes 30-400 certified for commercial/industrial heating application
- 82% - 84% Thermal efficiency
- 50-60°F Temperature rise range
- Serpentine titanium stabilized heat exchanger design
- 115/1/60 Supply voltage
- Transformer for 24-volt controls
- Integrated circuit board with diagnostic indicator lights
- Direct ignition with 100% shutoff
- Single stage gas valve with external gas service connection
- 4-point and 2-point Suspension
- External terminal strip connector for 24-volt wiring
- Easy DIP selectable fan on and off - time delay

REFERENCE: For additional technical information, request a technical catalog from your Reznor Sales Agent.

Size	30	45	60	75	100	125	150	175	200	225	250	300	350	400
Model UDAP	\$714	\$742	\$782	\$810	\$937	\$1,066	\$1,125	\$1,250	\$1,339	\$1,447	\$1,557	\$1,881	\$2,135	\$2,297
Shipping Weight (lbs)	61	66	74	79	118	123	204	219	219	245	257	321	346	358

Factory-Installed Options

FUEL TYPE		STD	-	-	-	-	-	-	-	-	-	-	-	-	-
Natural Gas	STD	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Propane Gas	AA2	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25	\$25
HEAT EXCHANGER MATERIAL		STD	-	-	-	-	-	-	-	-	-	-	-	-	-
Aluminized	STD	-	-	-	-	-	-	-	-	-	-	-	-	-	-
409 Stainless	AC2	\$151	\$160	\$199	\$220	\$233	\$252	\$275	\$286	\$309	\$352	\$469	\$469	\$659	\$682
316 Stainless	AC4	\$275	\$303	\$319	\$396	\$547	\$672	\$927	\$968	\$1,180	\$1,210	\$1,548	\$1,650	\$1,810	\$2,066
GAS CONTROL		STD	-	-	-	-	-	-	-	-	-	-	-	-	-
1-Stage Valve	STD	-	-	-	-	-	-	-	-	-	-	-	-	-	-
2-Stage Valve	AG2	■	■	■	\$160	\$160	\$160	\$160	\$160	\$160	\$160	\$160	\$160	\$160	\$160
VOLTAGE		STD	-	-	-	-	-	-	-	-	-	-	-	-	-
115/1/60	STD	-	-	-	-	-	-	-	-	-	-	-	-	-	-
208/1/60	AK2	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41
230/1/60	AK3	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41	\$41
TYPE OF FAN MOTOR		STD	-	-	-	-	-	-	-	-	-	-	-	-	-
Open	STD	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Totally Enclosed 115 volt only	AL14	■	■	■	■	\$66	\$66	\$35	\$35	\$35	\$21	\$21	\$27	\$27	\$27
Motor HP	STD	0.02	0.03	0.03	0.06	1/30	1/20	1/6	1/6	1/6	1/4	1/4	1/2	1/2	1/2
	AL14	■	■	■	■	1/4	1/4	1/4	1/4	1/4	1/4	1/4	1/2	1/2	1/2
COMMON VENT ^A		AV6	-	-	-	-	-	■	■	■	■	■	■	■	■
2 Heaters or with other Appliance	AV6	-	-	-	-	-	-	■	■	■	■	■	■	■	■
Size		30	45	60	75	100	125	150	175	200	225	250	300	350	400

^A Order Option AV6 when venting unit with other Category I gravity vented gas appliance. See Common Vent Venting Manual for complete details.

Field-Installed Options

Size		30	45	60	75	100	125	150	175	200	225	250	300	350	400
VENT CAP	CC1	\$28	\$28	\$28	\$28	\$28	\$28	\$34	\$34	\$34	\$34	\$34	\$37	\$37	\$37

VERTICAL LOUVERS AND DOWNTURN NOZZLES	Vertical Louvers	CD1	\$31	\$31	\$31	\$31	\$32	\$38	\$40	\$40	\$41	\$41	\$48	\$48	\$57	\$57
	Nozzle with 25° to 65° Variable Air Deflection Range	CD2	\$52	\$52	\$52	\$55	\$55	\$55	\$61	\$61	\$63	\$64	\$64	\$64	\$67	\$67
	Nozzle with 50° to 90° Variable Air Deflection Range	CD3	\$99	\$99	\$99	\$105	\$105	\$105	\$117	\$117	\$121	\$121	\$123	\$123	\$129	\$129
	CD2 Nozzle with Vertical Louvers	CD4	\$89	\$89	\$89	\$92	\$90	\$98	\$106	\$106	\$109	\$117	\$117	\$117	\$129	\$129

MANUAL SHUTOFF VALVE^B	Natural Gas or Propane	CE1	\$29	\$29	\$29	\$29	\$29	\$29	\$29	\$29	\$29	\$29	\$40	\$40	\$40	\$40
---	------------------------	------------	------	------	------	------	------	------	------	------	------	------	------	------	------	------

STEPDOWN TRANSFORMER	230/115	CG2	\$235	\$296	\$296	\$296	\$296	\$452	\$296	\$296	\$452	\$549	\$549	\$626	\$626	\$626
	460/115	CG4	\$235	\$296	\$296	\$296	\$296	\$452	\$296	\$296	\$452	\$549	\$549	\$626	\$626	\$626

CEILING HANGER KIT	Adapt 2 Point 3/8" hanger to 2 - 1" threaded pipe	CK8	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23	\$23
	Adapt 4 point 3/8" hanger to 2 - 1" threaded pipe	CK10	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30	\$30
	Low ceiling mount, angle brackets (does not include hanger rods)	CK22	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47	\$47
Size			30	45	60	75	100	125	150	175	200	225	250	300	350	400

ALUMINUM TAPE	1"x10 yds, 550°F, for vent pipe	FA1	\$40
----------------------	---------------------------------	------------	------

THERMOSTATS AND ACCESSORIES

One-Stage, 24 Volt	40-80°F temperature range	CL1	\$50	
	40-80°F temperature range with fan switch	CL2	\$67	
	40-90°F temperature range	CL3	\$70	
Two-Stage Heating, 24 Volt	2-stage heating	Use with Option AG2 or use 2nd Stage to energize fan relay (air recirculation)	CL7	\$132
	2-stage heating with fan switch		CL18	\$153
Multiple Heater Control - maximum of six units		Controller Unit	CL31	\$115
		Remote Unit	CL32	\$27
Thermostat Guard with Locking Cover		(does not fit CL3)	CM1	\$56
Thermostat Bracket Assembly		for unit mounted thermostat	CM3	\$26

FIELD INSTALLED HIGH ALTITUDE ADJUSTMENT KIT	For unit installed above 6,000 ft (2000 M)	DJ20	\$25
---	--	-------------	------

^B Refers to pipe connection size, not gas service line size.