### **IMPORTANT**

- Always include complete heater model and serial number so that any specification change can be considered for parts shipment. It can save time and expense.
- 2. Specifications are subject to change without notice.
- 3. We reserve the right to substitute functional replacements.
- 4. Order either by Kit or Component Part No.



## Functional Replacement Pilots

Parts Form RGM 701-B Obsoletes Form 701-A


Service Data

REZNOR Inomas@Betts	APPLIES TO:	,
Quick Reference Replaceme (Refer to Figures 1-12, pages 1-4, for ill)		

Quick Reference Replacement Pilot Kit Selection Table (Refer to Figures 1-12, pages 1-4, for illustrations and component part numbers.)							
Type of						ark Pilat	Kite
Heater	Widder Designation 5/51zes	Natural Propane Figure Natural Propane					
Infrare d	TR, TR-H 50	_	_	_	110854	110854	2
	TR, TR-H 75-200	_	_	_	110853	110853	2
Unit	F, B 25-400	110851	110852	1	110853	110854	2
Heaters	FE, BE 25-400	_	_	_	110853	110854	2
	UA, XL, XLB, CXL, CXLB 30 - 105	110855	110856	3	110857	110858	4
	XL, XLB, CXL, CXLB 125 - 400	110859	110860	5	110861	110862	6
	EEXL, EEXLB, CEEXL, CEEXLB 30-105	-	_	_	110857	110858	4
	EEXL, EEXLB, CEEXL, CEEXLB 125-400	ı	ı	_	110861	110862	6
	SCA, SCB prior to Series 6	-	-	_	110861	110862	6
	SCA, SCB Series 6	_	_	_	131457	131458	8
Duct	EEDU, HEEDU Series 6	_	_	_	110853	110854	2
Furnaces	EEDU, HEEDU prior to Series 6	_	_	_	110861	110862	6
and	X, XA, XB, XC, XD, XE, XG, XJ, PAK, DFAH prior to 9/73	110863	110864	8	_	_	_
Packages	X, XA, XB, XC, XD, XE, XG, XJ, PAK, DFAH, CX, CXE,	110859	110860	5	110861	110862	
	CPAK beginning 9/73	110059	110900	5	110901	110802	6
(Also	SC, SCE Series 6	_	_	_	131457	131458	8
applies to	RX, REB, RXE, RXJ, CRX, CREB, CRXE, RPAK, CRPAK;						
Models with	SC, SCE, SCJ prior to Series 6; RPV, RPVE, RPBE,						
prefix "H")	RPVAK, CRPV, CRPVE, CRPBE, CRPVAK Series 6; RG,	_	_	_	110861	110862	6
	CRG, RP, CRP, RGB, CRGB, RPB, CRPB, RGBL,						
	CRGBL, RPBL, CRPBL, SSCBL						
	RPV, RPBE, RPVE, RPVAK, RPVJ, CRPV, CRPBE,				=		
	CRPVE, CRPVAK prior to Series 6	_	_	_	110865	110866	9
Heating/	RCG 7-1/2, 10 ton	_	_	_	110865	110866	9
Cooling	RCG 2 - 5 ton - with vertical pilot	_	_	_	110867	110868	10
	- with horizontal pilot	_	_	_	110861	110862	6
Direct	ADF, ADFH with hot surface ignition	_	_	_	120048	120048	11
Fire d	RDF - with spark ignition and flame probe	_	_	_	110869	110869	11
	- with spark ignition and ultraviolet sensor	_	_	_	110918	110918	11
	- with hot surface ignition	_	_	_	120048	120048	11
	DV with hot surface ingition	_	_	_	120048	120048	11
	DFA with hot surface ignition	-	_	_	120048	120048	11

①If the replacement pilot changes with the introduction of a Model Series, the Series is indicated in the Selection Table. The Series indicator is on the heater rating plate; it is the suffix number on the Model Size (Ex: SC400-6; "6" is the Series).


### **Pilot Kits and Components**



Replacement		Natural Gas - P/N 110851
Pilot Kits		Propane Gas - P/N 110852
Code P/N		Component Description
1 96360		Natural Gas Pilot Assembly with orifice, pilot tubing, and
		thermocouple; less fitting (Johnson #J994HKA-9731-715)
96361		Propane Gas Pilot Assembly with orifice, pilot tubing, and
		thermocouple; less fitting (Johnson #J994HKA-9733-410)
2	103034	Natural Gas Orifice only, Johnson #9731-715 (brass)
98695 Propane Gas Orifice on		Propane Gas Orifice only, Johnson #9733-410 (black)
3 <b>98698</b> Pilot Tubing, 1/8" x		Pilot Tubing, 1/8" x O.D. x 18" long, Johnson #B10499-995-11
97572 Compression Fi		Compression Fitting, FTG75 (2 required when replacing pilot tubing)
4 84761		Thermocouple, 24", #K15FA-24D

②Spark pilot kits for all indirect-fired products are for use with Model G60, G65, G67 or G770 ignition controllers only. Pilot kits are not available for other spark ignition systems used on indirect-fired products.

Figure 2 - Vertical
Spark Pilot for Unit
<b>Heater Models F/FE/B/</b>
BE, Infrared Models
TR/TR-H, and Duct
<b>Furnace Models EEDU/</b>
<b>HEEDU Series 6</b>



-	Donlo		Modela E/EE/D/DE	Notural Cos I	D/N 110052, Duomomo Cog D/N 110054		
_			Models F/FE/B/BE		P/N 110853; Propane Gas - P/N 110854		
Pilot Kits		Kits	Model TR 50		Natural Gas - P/N 110854; Propane Gas - P/N 110854		
			<b>Models TR 75-200</b>	Natural Gas - I	P/N 110853; Propane Gas - P/N 110853		
			Models (H)EEDU	Natural Cas I	P/N 110853; Propane Gas - P/N 110854		
			Series 6	Natural Gas - 1/N 110033, 110pane Gas - 1/N 110034			
	Code	P/N	Application	Gas	Component Description		
Ī	1	97534	F/FE/B/BE and	Natural	Pilot Assembly with orifice, pilot tubing, and		
			(H)EEDU Series 6		flame rod; less flame sensor lead and fitting		
			TR 75-200	Natural & Propane	(Johnson #J982HKW-9731-715)		
		97535	F/FE/B/BE and	Propane	Pilot Assembly with orifice, pilot tubing, and		
			(H)EEDU Series 6		flame rod; less flame sensor lead and fitting		
			TR 50	Natural & Propane	(Johnson #J982HKW-9733-410)		
	2	103034	F/FE/B/BE and	Natural	Orifice only, Johnson #9731-715 (brass)		
	98695		(H)EEDU Series 6	rvaturar			
			TR 75-200	Natural & Propane			
			F/FE/B/BE and	Dronono	Orifice only, Johnson #9733-410 (black)		
			(H)EEDU Series 6	Propane			
			TR 50	Natural & Propane			
•	3	98698			Pilot Tubing, 1/8" OD x 18" lg, Johnson		
					#B10499-995-11		
	97572		F/FE/B/BE/TR/	Natural & Propane	Compression Fitting, FTG75 (2 required		
			(H)EEDU Series 6	*	when replacing pilot tubing)		
4 98697		98697	\		Flame Rod, Johnson #Y75AA-10		
-	5	97575			Flame Sensor Lead, 21"		

Figure 3 - Horizontal Match Lit Pilot for Models UA, XL, XLB, CXL, CXLB 30 - 105



)			
Replacement		Natural Gas - P/N 110855	
Pilot I	Kits	Propane Gas - P/N 110856	
Code P/N		Component Description	
1	40964	Natural Gas Pilot Assembly with	
		orifice; less pilot tubing, less	
		thermocouple (Baso #J999HKA4213)	
40420		Propane Gas Pilot Assembly with	
		orifice; less pilot tubing, less	
		thermocouple (Baso #J999HKA4207)	
2 40966		Natural Gas Orifice only, #4213	
	40965	Propane Gas Orifice only, #4207	
3 5145		Pilot Tubing, 22" long	
	9664	Nut with breakaway ferrule (2 required	
		when replacing pilot tubing)	
4 84761		Thermocouple, TC2-24"	

Figure 4 - Horizontal Spark Pilot for Models EEXL, EEXLB, CEEXL, CEEXLB 30 - 105. May also be used on XL, XLB, CXL, CXLB when equipped with G60, G65 or G67 ignition controller (with or without Serial No. Suffix "B")



Replacement		Natural Gas - P/N 110857
Pilot Kits		Propane Gas - P/N 110858
Code P/N		Component Description
1	93971	Natural Gas Pilot Assy with orifice and high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J983HKW7715)
	93972	Propane Gas Pilot Assy with orifice and high tension lead; less pilot
		tubing, less flame probe, less sensor lead (Baso #J983HKW4709)
2 93973		Natural Gas Orifice only, #7715
93974		Propane Gas Orifice only, #4709
3 <b>5145</b>		Pilot Tubing, 22" long
9664		Nut with breakaway ferrule (2 required when replacing pilot tubing)
4 50450		Sensor lead, 16" lg
5 43594		Flame probe, Y75BA

Above pilot replaces Baso #J987HKW, natural gas P/N 50449 and propane gas P/N 51330. Also replaces General Controls #26C27113 with 16" high tension lead, natural gas pilot P/N 64463 and propane gas P/N 64464; and General Controls #26C27113 with 24" high tension lead, natural gas pilot P/N 73614 and propane pilot P/N 73615

Replacement		Natural Gas - P/N 110859			
Pilot Kits		Propane Gas - P/N 110860			
Code	P/N	Component Description			
1	17890	Natural Gas Pilot with orifice; less pilot tubing, less thermocouple (Baso	#J963HXA6218)		
	46136	Propane Gas Pilot with orifice; less pilot tubing, less thermocouple (Bas-	o #J963HXA4211)		
2	46392	Natural Gas Orifice only, #6218			
	42089	Propane Gas Orifice only, #4211 This pile			
3	7671	Pilot Tubing, 26" lg for X Series may be u			
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing) in place			
3A	5145	Pilot Tubing, 22" lg for XL, XLB, CXL, CXLB 125-400			
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)	#26C23114.		
4	84761	Thermocouple TC2, 24" lg for X Series			
4A	84760	Thermocoup le TC2, 18" lg for XL, XLB, CXL, CXLB 125-400			


Form 701, Page 2

### Figure 6 - Horizontal Spark Pilots for Models

XL, XLB, CXL, CXLB 125-400

EEXL, EEXLB, CEEXL, CEEXLB 125-400; EEDU, HEEDU prior to Series 6

Starting 9/73 for X, XA, XB, XC, XD, XE, XG, XJ, PAK, DFAH, CX, CXE, CPAK
RX, REB, RXE, RXJ, CRX, CREB, CRXE, RPAK, CRPAK; SC, SCA, SCB, SCE, SCJ
Prior to Series 6; RPV, RPVE, RPBE, RPVAK, CRPV, CRPVE, CRPBE, CRPVAK
Series 6; RG, CRG, RP, CRP, RGB, CRGB, RPB, CRPB, RGBL, CRGBL, RPBL,
CRPBL, SSCBL



RCG 2 through 5 ton with horizontal pilot

#### **NOTES:**

- Horizontal spark pilots for ignition systems other than G60, G65, G67 and G770 are no longer available.
- Kits also apply to models listed with the prefix "H"

\*Included in all kits. Used only with the above models equipped with any Model G60 ignition controller, a Model G67BG-2, or a Model G67NG-2. Not used with ignition controller Models G67BG-5 and G770NGC-4. See Instructions on page 4.

 This pilot replaces Baso #J991HXW, natural gas P/N 45150, propane P/N 45141; #J994HXW, natural gas P/N 47303, propane P/N 47384. May be used as a substitution for J993HXW and J999HXW.

Replacement		Natural Gas - P/N 110861
Pilot Kits		Propane Gas - P/N 110862
Code P/N		Component Description
1	61145	Natural Gas Pilot Assy with orifice, high tension lead, flame probe;
		less pilot tubing, less flame sensor lead (Baso #J992HXW7221)
	61146	Propane Gas Pilot Assy with orifice, high tension lead, flame probe;
		less pilot tubing, less flame sensor lead (Baso #J992HXW9817)
2	63088	Natural Gas Orifice only, #7221
	37801	Propane Gas Orifice only, #4209
3	5145	Pilot Tubing, 22" lg
9664		Nut with breakaway ferrule (2 required when replacing pilot tubing)
4 50450		Sensor lead, 16" lg
5*	112647	Crimp-on, 90° Rajah terminal connector
6*	112648	90° Boot Terminal Protector

\*See instructions on page 4.

Figure 7 - Vertical Spark Pilot for Models SC, SCA, SCB, SCE Series 6

Replacement Natural Gas - P/N 131457

1
V T W
2 3
-5
3

			Natural Gas - P/N 151457
	Pilot Kits		Propane Gas - P/N 131458
	Code	P/N	Component Description
	1	125251	Natural Gas Pilot Assy with orifice, pilot
			tubing, flame probe; less flame sensor lead
			and fitting (J/C J981HKW 9731-713)
٠		125671	Propane Gas Pilot Assy with orifice, pilot
			tubing, flame probe; less flame sensor lead
			and fitting (J/C J981HKW 9715-413)
	2	93973	Natural Gas Orifice only, #9731-713 (brass)
		126024	Propane Gas Orifice only, #9715-413 (black)
	3	98698	Pilot Tubing, 1/8" OD x 18" lg (J/C #B10499-
			995-11)
		97572	Compression Fitting FTG75 (2 required
			when replacing pilot tubing)
	4	126104	Flame probe, J/C Y75AA-2
	5	126101	Auxiliary flame probe with bracket, J/C Y75
			GB-1
	6	125401	(2) Sensor lead assy, 18 ga. x 14", 150°C

Lit Pilot for
Models X, XA,
XB, XC, XD,
XE, XG, XJ,
PAK, DFAH
prior to 9/73
1
400
S. March
/11 %
2 1 4

Figure 8 -


Vertical Match

prior	to 9/13
1	<u>kı— 4</u>
7	-
2	1
	7
3	1

Replacement		Natural Gas - P/N 110863	
Pilot Kits		Propane Gas - P/N 110864	
Code P/N		Component Description	
1	9661	Natural Gas Pilot Assy	
		with orifice; less pilot	
		tubing, less thermocouple	
		(Baso J915HHA6221)	
	30126	Propane Gas Pilot Assy	
		with orifice; less pilot	
		tubing, less thermocouple	
		(Baso J915HHA4211)	
2	44048	Natural Gas Orifice only,	
		#6221	
	42089	Propane Gas Orifice only,	
		#4211	
3	7671	Pilot Tubing, 26" lg	
	9664	Nut with breakaway ferrule	
		(2 required when replacing	
		pilot tubing)	
4	84761	Thermocouple, TC2, 24" lg	

Figure 9 - Vertical Spark Pilot for Models RPV, RPBE, RPVE, RPVJ, RPVAK, HRPV, HRPBE, HRPVE, CRPV, HCRPV, CRPBE, HCRPBE, CRPVE, HCRPVE; CRPVAK prior to Series 6 and RCG 7-12/, 10 ton equipped with G60

or G67 ignition Controller




\*See Instructions, page 4.

**NOTE:** Vertical spark pilots for ignition systems other than G60 and G67 are no longer available.


E; CRPVAK prior to Series 6 and RCG 7-12/, 10 ton equipped with G60			
Replacement		Natural Gas - P/N 110865	
Pilot Kits		Propane Gas - P/N 110866	
Code	ode P/N Component Description		
1	41775 Natural Gas Pilot Assy with orifice, high tension lead; less pilot		
		tubing, less flame probe, less sensor lead (Baso #J999HHW6221)	
	44673	Propane Gas Pilot Assy with orifice, high tension lead; less pilot	
		tubing, less flame probe, less sensor lead (Baso #J999HHW4209)	
2	44048	48 Natural Gas Orifice only, #6221	
	37801	Propane Gas Orifice only, #4209	
3	92848	Sensor lead assembly, 16" lg and 21" lg wires (not illustrated)	
4	43594	(2) Flame probe Y75BA-3	
5	44678	Bracket Y59DD-1	
6*	112647	Crimp-on, 90° Rajah terminal connector	
7*	112648	90° Boot Terminal Protector	
8	7671	Pilot tubing 26" lg (not illustrated)	
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)	
		Mfg #121122 Page 2	

Figure 10 - Vertical Spark Pilot		
for Models RCG 2 - 5 ton with		
Vertical Dilet		



Replacement		Natural Gas - P/N 110867	
Pilot Kits		Propane Gas - P/N 110868	
Coo	de <b>P/N</b>	Component Description	
1	47484	Natural Gas Pilot with orifice, high tension lead and built-in flame probe; less	
		pilot tubing, less sensor lead (Baso #J993HHW6221)	
	47485	Prop ane Gas Pilot with orifice, high tension lead and built-in flame probe; less	
		pilot tubing, less sensor lead (Baso #J993HHW4211)	
2	44048	Natural Gas Orifice only, #6221	
	42089	Prop ane Gas Orifice only, #4211	
3	44183	Sensor lead, 38" lg	
4	7671	Pilot tubing 26" lg	
	9664	Nut with breakaway ferrule (2 required when replacing pilot tubing)	
5*	112647	Crimp-on, 90° Rajah terminal connector	
6*	112648	90° Boot Terminal Protector	

Figure 11 - Pilot Systems used on Direct-Fired Models RDF/ADF/ADFH/DFA/DV



\*P/N 135435 is a replacement flame sensor only kit for ADF/ ADFH units manufactured prior to 11/94.

sed on Direct-Fired Models RDF/ADF/ADFH/DFA/DV				
	Replac	ement	w/Flame Probe - P/N 110869 (Includes Codes 1, 2, 3)	RDF with spark pilot
Pilot Kits		Kits	w/Ultraviolet Sensor - P/N 110918 (Includes Codes 1, 2, 4)	RDF with spark pilot
			w/Hot Surface Ignition - P/N 120048 (Includes	ADF/DFA/RDF/DV with
	Codes 5, 6, 7, and 8)		Codes 5, 6, 7, and 8)	hot surface ignition
	Code	P/N	Component Description	Applies to
	1		Pilot Supply Connection including: (1) brass elbow,	
			<b>P/N 93388</b> ; (3) connectors, <b>P/N 95188</b> ; (1) long nut,	
			P/N 95189	RDF Models
	2	87936	Sp ark Plug, 27750-1-31, M axon #18075	with a spark pilot
	3	87937	Flame Probe, Auburn AA67-7892-1 - Standard on	and either a probe or
			units with date code prior to ANI (9/88)	ultraviolet
	4	89411	Ultraviolet Minipeeper, #C7027A - Standard on units	flame sensor
			with date code from ANI (9/88) through AVB (2/96) -	
			optional on prior units	
	5	122840	Pilot Plate and Tubing Assembly	ADF/ADFH*; DFA;
	6	134706*	Flame Sensor, J/C #Y75M K-1D	DV; and RDF with
	7	121865	Ignitor, Norton #401E	hot surface
	8	121730	Pilot Bushing	ignition

**Hot Surface Ignition Kits** below include all components needed to change **RDF** units from a spark pilot system with either a flame probe or ultraviolet sensor to hot surface ignition

- for an RDF unit with a 200VA Transformer P/N 146268
- for a 115V RDF unit with an 80VA transformer P/N 146318
- for a 208V RDF unit with an 80VA transformer P/N 146319
- for a 240V, 480V, or 575V RDF unit with an 80VA transformer  $\mbox{P/N}$  146320

Note: Model, Serial No., and Wiring Diagram No. MUST be provided when ordering these kits.

# Instructions for connecting ignitor lead on replacement spark pilots to Model G60 and G67 ignition controllers (applies to Pilot Kits in Figures 6, 9, and 10):




Crimp-on, 90° Rajah Terminal Connector, P/N 112647



Protective Boot, P/N 112648

Effective with replacement pilots purchased 9/91, these parts are required (in the kit or separately) when the replacement pilot is for heater Models listed in Figures 6, 9 and 10 equipped with a Model G60 or G67BG-NG-2 ignition controller. (Note: These parts are not required when the ignition controller is a Model G67BG-5 or G770NGC-4.)

- Identify the ignitor wire attached to the pilot electrode. Slip the 90° protective boot on to the wire, as illustrated →.
- 2. On the "open" leg of the 90° crimp-on terminal (P/N 112647), locate a flat, triangular spike tab punched in the metal. With the tip of a small, straight screwdriver, force the spike tab toward the inside of the connector. Straighten the tab to a vertical position.
- 3. Insert the ignitor wire into that same connector leg (just to the 90° bend) and push the wire onto the protruding spike tab, making sure that the tab penetrates the insulation. (Do not strip the ignitor wire.) Using a crimping tool or pliers, squeeze the sides of the terminal to form a "C" shape. The ignitor wire should now be firmly held by the terminal.



 Slide the protective boot over the terminal. Holding the boot, attach the 90° Rajah terminal to the ignitor lead Rajah connector on the Model G60 or G67BG/NG-2 ignition controller.

