

Electrical Data

Model	Furnace	Power	Compressor		Evaporator Blower Motor		Condenser Fan Motor(s)				Comb Blower Motor	Unit RLA	MCA*	Max. Fuse Size*
			RLA	LRA	HP	FLA	No.	HP	FLA	FLA				
PCC-071	100-125	208/230-3-60	15.4	123.0	1/2	2.0	1	1/2	3.5	—	0.8	20.9	25.0	35
PCC-071		460-3-60	7.7	62.0	1/2	1.0	1	1/2	1.8	—	0.32	10.5	13.0	20
PCC-071		208/230-3-60	15.4	123.0	3/4	2.8	1	1/2	3.5	—	0.8	21.7	26.0	40
PCC-071		460-3-60	7.7	62.0	3/4	1.4	1	1/2	1.8	—	0.32	10.9	13.0	20
PCC-071		208/230-3-60	15.4	123.0	1	3.6	1	1/2	3.5	—	0.8	22.5	27.0	40
PCC-071		460-3-60	7.7	62.0	1	1.8	1	1/2	1.8	—	0.32	11.3	14.0	20
PCC-101	100-175	208/230-3-60	26.2	189.0	1/2	2.0	1	1	6.2	—	0.8	34.4	41.0	60
PCC-101		460-3-60	14.3	94.0	1/2	1.0	1	1	3.1	—	0.32	18.4	22.0	35
PCC-101		208/230-3-60	26.2	189.0	3/4	2.8	1	1	6.2	—	0.8	35.2	42.0	60
PCC-101		460-3-60	14.3	94.0	3/4	1.4	1	1	3.1	—	0.32	18.8	23.0	35
PCC-101		208/230-3-60	26.2	189.0	1	3.6	1	1	6.2	—	0.8	36.0	43.0	60
PCC-101		460-3-60	14.3	94.0	1	1.8	1	1	3.1	—	0.32	19.2	23.0	35
PCC-141	150-225	208/230-3-60	38.5	255.0	1	3.6	1	1	6.2	—	0.8	48.3	58.0	90
PCC-141		460-3-60	18.8	127.0	1	1.8	1	1	6.2	—	0.32	26.8	32.0	50
PCC-141		208/230-3-60	38.5	255.0	1-1/2	4.6	1	1	6.2	—	0.8	49.3	59.0	90
PCC-141		460-3-60	18.8	127.0	1-1/2	2.3	1	1	6.2	—	0.32	27.3	33.0	50
PCC-141		208/230-3-60	38.5	255.0	2	7.0	1	1	6.2	—	0.8	51.7	62.0	90
PCC-141		460-3-60	18.8	127.0	2	3.5	1	1	6.2	—	0.32	28.5	34.0	50
PCC-181	150-300	208/230-3-60	47.1	318.0	1	3.6	2	1	6.2	3.4	0.8	60.3	72.0	110
PCC-181		460-3-60	22.8	158.0	1	1.8	2	1	6.2	1.7	0.32	32.5	39.0	60
PCC-181		208/230-3-60	47.1	318.0	2	7.0	2	1	6.2	3.4	0.8	63.7	76.0	110
PCC-181		460-3-60	22.8	158.0	2	3.5	2	1	6.2	1.7	0.32	34.2	40.0	60
PCC-181		208/230-3-60	47.1	318.0	3	8.8	2	1	6.2	3.4	0.8	65.5	78.0	110
PCC-181		460-3-60	22.8	158.0	3	4.4	2	1	6.2	1.7	0.32	35.1	41.0	50
PCC-201	150-350	208/230-3-60	48.2	275.0	1	3.6	2	1	6.2	3.4	0.8	61.4	74.0	110
PCC-201		460-3-60	23.6	138.0	1	1.8	2	1	6.2	1.7	0.32	33.3	40.0	60
PCC-201		208/230-3-60	48.2	275.0	2	7.0	2	1	6.2	3.4	0.8	64.8	77.0	125
PCC-201		460-3-60	23.6	138.0	2	3.5	2	1	6.2	1.7	0.32	35.0	41.0	60
PCC-201		208/230-3-60	48.2	275.0	3	8.8	2	1	6.2	3.4	0.8	66.6	79.0	125
PCC-201		460-3-60	23.6	138.0	3	4.4	2	1	6.2	1.7	0.32	35.9	42.0	60
PCC-271	150-400	208/230-3-60	86.0	428.0	2	7.0	2	1	6.2	3.4	0.8	102.6	124.0	200
PCC-271		460-3-60	43.0	214.0	2	3.5	2	1	6.2	1.7	0.32	54.4	66.0	100
PCC-271		208/230-3-60	86.0	428.0	3	8.8	2	1	6.2	3.4	0.8	104.4	126.0	200
PCC-271		460-3-60	43.0	214.0	3	4.4	2	1	6.2	1.7	0.32	55.3	66.0	100
PCC-271		208/230-3-60	86.0	428.0	5	14.0	2	1	6.2	3.4	0.8	109.6	132.0	200
PCC-271		460-3-60	43.0	214.0	5	7.0	2	1	6.2	1.7	0.32	57.9	69.0	110
PCC-361	150-400	208/230-3-60	118.0	470.0	3	8.8	4	1	6.2	3.4	0.8	143.2	173.0	250
PCC-361		460-3-60	59.0	235.0	3	4.4	4	1	6.2	1.7	0.32	74.7	90.0	125
PCC-361		208/230-3-60	118.0	470.0	5	14.0	4	1	6.2	3.4	0.8	148.4	178.0	250
PCC-361		460-3-60	59.0	235.0	5	7.0	4	1	6.2	1.7	0.32	77.3	93.0	150
PCC-361		208/230-3-60	118.0	470.0	7-1/2	24.0	4	1	6.2	3.4	0.8	158.4	188.0	300
PCC-361		460-3-60	59.0	235.0	7-1/2	10.0	4	1	6.2	1.7	0.32	80.3	96.0	150

* MCA - Minimum Circuit Ampacity Max. Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker
Please contact factory to verify critical data.

Code	Unit Voltage	Motor
5	208/3/60	AK5
6	230/3/60	AK6
7	460/3/60	AK7

[Return to Packaged Cooling Catalog \(C-PC\) Table of Contents](#)