

Engineering/Application Information (cont'd) Electrical Data

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**	
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA
060	087	208/230-3-60	15.4	1	--	--	1/2	3.0	3/4	4.3	1	8.0	1	27	35	40	50
		460-3-60	10.0	1	--	--	1/2	1.5	3/4	2.0	1	4.1	1	16	20	25	30
		208/230-3-60	15.4	1	--	--	3/4	2.9	3/4	4.3	1	8.0	1	26	34	40	50
		460-3-60	10.0	1	--	--	3/4	1.3	3/4	2.0	1	4.1	1	16	20	25	30
		208/230-3-60	15.4	1	--	--	1	3.7	3/4	4.3	1	8.0	1	27	35	40	50
		460-3-60	10.0	1	--	--	1	1.7	3/4	2.0	1	4.1	1	16	20	25	30
		208/230-3-60	15.4	1	--	--	1-1/2	5.6	3/4	4.3	1	8.0	1	29	37	40	50
		460-3-60	10.0	1	--	--	1-1/2	2.7	3/4	2.0	1	4.1	1	17	21	25	30
		208/230-3-60	15.4	1	--	--	2	7.0	3/4	4.3	1	8.0	1	31	39	45	50
		460-3-60	10.0	1	--	--	2	3.5	3/4	2.0	1	4.1	1	18	22	25	30
096	123	208/230-3-60	15.4	1	10.6	1	1/2	3.0	3/4	4.3	1	8.0	1	37	45	50	60
		460-3-60	10.0	1	4.2	1	1/2	1.5	3/4	2.0	1	4.1	1	20	24	30	35
		208/230-3-60	15.4	1	10.6	1	3/4	2.9	3/4	4.3	1	8.0	1	37	45	50	60
		460-3-60	10.0	1	4.2	1	3/4	1.3	3/4	2.0	1	4.1	1	20	24	30	35
		208/230-3-60	15.4	1	10.6	1	1	3.7	3/4	4.3	1	8.0	1	38	46	50	60
		460-3-60	10.0	1	4.2	1	1	1.7	3/4	2.0	1	4.1	1	20	25	30	35
		208/230-3-60	15.4	1	10.6	1	1-1/2	5.6	3/4	4.3	1	8.0	1	40	48	50	60
		460-3-60	10.0	1	4.2	1	1-1/2	2.7	3/4	2.0	1	4.1	1	21	26	30	35
		208/230-3-60	15.4	1	10.6	1	2	7.0	3/4	4.3	1	8.0	1	41	49	50	60
		460-3-60	10.0	1	4.2	1	2	3.5	3/4	2.0	1	4.1	1	22	26	30	35
120	147	208/230-3-60	15.4	2	--	--	1/2	3.0	3/4	4.3	1	8.0	1	46	54	60	70
		460-3-60	10.0	2	--	--	1/2	1.5	3/4	2.0	1	4.1	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	3/4	2.9	3/4	4.3	1	8.0	1	46	54	60	70
		460-3-60	10.0	2	--	--	3/4	1.3	3/4	2.0	1	4.1	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	1	3.7	3/4	4.3	2	8.0	1	47	55	60	70
		460-3-60	10.0	2	--	--	1	1.7	3/4	2.0	2	4.1	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	1-1/2	5.6	3/4	4.3	2	8.0	1	49	57	60	70
		460-3-60	10.0	2	--	--	1-1/2	2.2	3/4	2.0	2	4.1	1	29	33	35	40
		208/230-3-60	15.4	2	--	--	2	7.0	3/4	4.3	2	8.0	1	50	58	60	70
		460-3-60	10.0	2	--	--	2	3.5	3/4	2.0	2	4.1	1	30	34	40	40
208/230-3-60	15.4	2	--	--	3	9.1	3/4	4.3	2	8.0	1	52	60	60	70		
460-3-60	10.0	2	--	--	3	4.2	3/4	2.0	2	4.1	1	31	35	40	45		
208/230-3-60	15.4	2	--	--	5	13.4	3/4	4.3	2	8.0	1	57	65	70	80		
460-3-60	10.0	2	--	--	5	6.6	3/4	2.0	2	4.1	1	33	37	40	45		

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data

Engineering/Application Information (cont'd)**Electrical Data (cont'd)**

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**	
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA
130	176	208/230-3-60	15.4	2	--	--	1/2	3.0	3/4	4.3	1	10.6	1	46	57	60	70
		460-3-60	10.0	2	--	--	1/2	1.5	3/4	2.0	1	4.2	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	3/4	2.9	3/4	4.3	1	10.6	1	46	57	60	70
		460-3-60	10.0	2	--	--	3/4	1.3	3/4	2.0	1	4.2	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	1	3.7	3/4	4.3	2	10.6	1	47	58	70	70
		460-3-60	10.0	2	--	--	1	1.7	3/4	2.0	2	4.2	1	28	32	35	40
		208/230-3-60	15.4	2	--	--	1-1/2	5.6	3/4	4.3	2	10.6	1	49	58	70	70
		460-3-60	10.0	2	--	--	1-1/2	2.7	3/4	2.0	2	4.2	1	29	33	35	40
		208/230-3-60	15.4	2	--	--	2	7.0	3/4	4.3	2	10.6	1	50	61	70	70
		460-3-60	10.0	2	--	--	2	3.5	3/4	2.0	2	4.2	1	30	34	40	40
		208/230-3-60	15.4	2	--	--	3	9.0	3/4	4.3	2	10.6	1	52	63	70	70
		460-3-60	10.0	2	--	--	3	4.3	3/4	2.0	2	4.2	1	31	35	40	45
208/230-3-60	15.4	2	--	--	5	13.4	3/4	4.3	2	10.6	1	57	68	70	80		
460-3-60	10.0	2	--	--	5	6.6	3/4	2.0	2	4.2	1	33	37	40	45		
135	162	208/230-3-60	18.7	1	15.4	1	1/2	3.0	3/4	4.3	1	8.0	1	50	58	60	70
		460-3-60	9.2	1	10.0	1	1/2	1.5	3/4	2.0	1	4.1	1	26	31	35	40
		208/230-3-60	18.7	1	15.4	1	3/4	2.9	3/4	4.3	1	8.0	1	50	58	60	70
		460-3-60	9.2	1	10.0	1	3/4	1.3	3/4	2.0	1	4.1	1	26	31	35	40
		208/230-3-60	18.7	1	15.4	1	1	3.7	3/4	4.3	2	8.0	1	51	59	70	70
		460-3-60	9.2	1	10.0	1	1	1.7	3/4	2.0	2	4.1	1	28	32	35	40
		208/230-3-60	18.7	1	15.4	1	1-1/2	5.6	3/4	4.3	2	8.0	1	53	61	70	70
		460-3-60	9.2	1	10.0	1	1-1/2	2.7	3/4	2.0	2	4.1	1	29	33	35	40
		208/230-3-60	18.7	1	15.4	1	2	7.0	3/4	4.3	2	8.0	1	54	62	70	70
		460-3-60	9.2	1	10.0	1	2	3.5	3/4	2.0	2	4.1	1	30	33	35	40
		208/230-3-60	18.7	1	15.4	1	3	9.0	3/4	4.3	2	8.0	1	56	64	70	70
		460-3-60	9.2	1	10.0	1	3	4.3	3/4	2.0	2	4.1	1	31	34	35	45
208/230-3-60	18.7	1	15.4	1	5	13.4	3/4	4.3	2	8.0	1	61	69	70	80		
460-3-60	9.2	1	10.0	1	5	6.6	3/4	2.0	2	4.1	1	33	36	40	45		
150	177	208/230-3-60	18.7	2	--	--	1/2	3.0	3/4	4.3	1	8.0	1	54	62	70	80
		460-3-60	9.2	2	--	--	1/2	1.5	3/4	2.0	1	4.1	1	26	31	35	40
		208/230-3-60	18.7	2	--	--	3/4	2.9	3/4	4.3	1	8.0	1	54	62	70	80
		460-3-60	9.2	2	--	--	3/4	1.3	3/4	2.0	1	4.1	1	26	30	35	40
		208/230-3-60	18.7	2	--	--	1	3.7	3/4	4.3	2	8.0	1	54	62	70	80
		460-3-60	9.2	2	--	--	1	1.7	3/4	2.0	2	4.1	1	27	31	35	40
		208/230-3-60	18.7	2	--	--	1-1/2	5.6	3/4	4.3	2	8.0	1	56	64	70	80
		460-3-60	9.2	2	--	--	1-1/2	2.7	3/4	2.0	2	4.1	1	28	32	35	40
		208/230-3-60	18.7	2	--	--	2	7.0	3/4	4.3	2	8.0	1	58	66	70	80
		460-3-60	9.2	2	--	--	2	3.5	3/4	2.0	2	4.1	1	28	33	35	40
		208/230-3-60	18.7	2	--	--	3	9.0	3/4	4.3	2	8.0	1	60	68	70	80
		460-3-60	9.2	2	--	--	3	4.3	3/4	2.0	2	4.1	1	29	33	35	40
208/230-3-60	18.7	2	--	--	5	13.4	3/4	4.3	2	8.0	1	65	73	80	90		
460-3-60	9.2	2	--	--	5	6.6	3/4	2.0	2	4.1	1	32	36	40	45		

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data

Engineering/Application Information (cont'd) Electrical Data (cont'd)

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**	
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA
160	206	208/230-3-60	18.7	2	--	--	1	3.7	3/4	4.3	2	10.6	1	54	65	70	80
		460-3-60	9.2	2	--	--	1	1.7	3/4	2.0	2	4.2	1	27	31	35	40
		208/230-3-60	18.7	2	--	--	1-1/2	5.6	3/4	4.3	2	10.6	1	56	67	70	80
		460-3-60	9.2	2	--	--	1-1/2	2.7	3/4	2.0	2	4.2	1	28	32	35	40
		208/230-3-60	18.7	2	--	--	2	7.0	3/4	4.3	2	10.6	1	58	68	70	80
		460-3-60	9.2	2	--	--	2	3.5	3/4	2.0	2	4.2	1	28	33	35	40
		208/230-3-60	18.7	2	--	--	3	9.0	3/4	4.3	2	10.6	1	60	70	70	80
		460-3-60	9.2	2	--	--	3	4.3	3/4	2.0	2	4.2	1	29	33	35	40
		208/230-3-60	18.7	2	--	--	5	13.4	3/4	4.3	2	10.6	1	65	75	80	90
460-3-60	9.2	2	--	--	5	6.6	3/4	2.0	2	4.2	1	32	36	40	45		
180	226	208/230-3-60	15.4	3	--	--	1	3.7	3/4	4.3	3	10.6	1	67	78	80	90
		460-3-60	10.0	3	--	--	1	1.7	3/4	2.0	3	4.2	1	40	44	50	50
		208/230-3-60	15.4	3	--	--	1-1/2	5.6	3/4	4.3	3	10.6	1	69	80	80	90
		460-3-60	10.0	3	--	--	1-1/2	2.7	3/4	2.0	3	4.2	1	41	45	50	50
		208/230-3-60	15.4	3	--	--	2	7.0	3/4	4.3	3	10.6	1	71	81	80	90
		460-3-60	10.0	3	--	--	2	3.5	3/4	2.0	3	4.2	1	42	46	50	50
		208/230-3-60	15.4	3	--	--	3	9.0	3/4	4.3	3	10.6	1	73	83	80	90
		460-3-60	10.0	3	--	--	3	4.3	3/4	2.0	3	4.2	1	43	47	50	50
		208/230-3-60	15.4	3	--	--	5	13.4	3/4	4.3	3	10.6	1	78	88	90	100
460-3-60	10.0	3	--	--	5	6.6	3/4	2.0	3	4.2	1	45	49	50	50		
195	241	208/230-3-60	15.4	2	18.7	1	1	3.7	3/4	6.3	3	10.6	1	71	81	80	100
		460-3-60	10.0	2	9.2	1	1	1.7	3/4	2.3	3	4.2	1	40	44	45	50
		208/230-3-60	15.4	2	18.7	1	1-1/2	5.6	3/4	4.3	3	10.6	1	73	83	90	100
		460-3-60	10.0	2	9.2	1	1-1/2	2.7	3/4	2.0	3	4.2	1	41	45	45	50
		208/230-3-60	15.4	2	18.7	1	2	7.0	3/4	4.3	3	10.6	1	74	85	90	100
		460-3-60	10.0	2	9.2	1	2	3.5	3/4	2.0	3	4.2	1	42	45	50	50
		208/230-3-60	15.4	2	18.7	1	3	9.0	3/4	4.3	3	10.6	1	76	87	90	100
		460-3-60	10.0	2	9.2	1	3	4.3	3/4	2.0	3	4.2	1	43	46	50	50
		208/230-3-60	15.4	2	18.7	1	5	13.4	3/4	4.3	3	10.6	1	81	92	90	110
460-3-60	10.0	2	9.2	1	5	6.6	3/4	2.0	3	4.2	1	45	49	50	50		
210	256	208/230-3-60	15.4	1	18.7	2	1		3/4	4.3	3	10.6	1	74	85	90	100
		460-3-60	10.0	1	9.2	2	1	13.0	3/4	2.0	3	4.2	1	38	43	45	50
		208/230-3-60	15.4	1	18.7	2	1-1/2	5.6	3/4	4.3	3	10.6	1	76	87	90	100
		460-3-60	10.0	1	9.2	2	1-1/2	2.7	3/4	2.0	3	4.2	1	39	44	45	50
		208/230-3-60	15.4	1	18.7	2	2	7.0	3/4	4.3	3	10.6	1	77	88	90	100
		460-3-60	10.0	1	9.2	2	2	3.5	3/4	2.0	3	4.2	1	40	45	45	50
		208/230-3-60	15.4	1	18.7	2	3	9.0	3/4	4.3	3	10.6	1	79	90	90	100
		460-3-60	10.0	1	9.2	2	3	4.3	3/4	2.0	3	4.2	1	41	45	50	50
		208/230-3-60	15.4	1	18.7	2	5	13.4	3/4	4.3	3	10.6	1	84	95	100	110
460-3-60	10.0	1	9.2	2	5	6.6	3/4	2.0	3	4.2	1	43	48	50	50		

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data

Engineering/Application Information (cont'd)**Electrical Data (cont'd)**

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**			
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA		
225	271	208/230-3-60	18.7	3	--	--	1		3/4	4.3	3	10.6	1	77	88	90	100		
		460-3-60	9.2	3	--	--	1	13.0	3/4	2.0	3	4.2	1	38	42	45	50		
		208/230-3-60	18.7	3	--	--	1-1/2	5.6	3/4	4.3	3	10.6	1	79	90	90	100		
		460-3-60	9.2	3	--	--	1-1/2	2.7	3/4	2.0	3	4.2	1	39	43	45	50		
		208/230-3-60	18.7	3	--	--	2	7.0	3/4	4.3	3	10.6	1	81	91	90	110		
		460-3-60	9.2	3	--	--	2	3.5	3/4	2.0	3	4.2	1	40	44	45	50		
		208/230-3-60	18.7	3	--	--	3	9.0	3/4	4.3	3	10.6	1	83	93	100	110		
		460-3-60	9.2	3	--	--	3	4.3	3/4	2.0	3	4.2	1	40	45	45	50		
225	271	208/230-3-60	18.7	3	--	--	5	13.4	3/4	4.3	3	10.6	1	88	98	100	110		
		460-3-60	9.2	3	--	--	5	6.6	3/4	2.0	3	4.2	1	43	47	50	50		
		"B" Size Cabinets																	
		165	223	208/230-3-60	16.0	2	--	--	1	13.0	3/4	4.3	2	10.6	1	48	60	60	70
				460-3-60	7.7	2	--	--	1	1.7	3/4	2.0	2	4.2	1	24	28	30	35
				208/230-3-60	16.0	2	--	--	1-1/2	5.6	3/4	4.3	2	10.6	1	49	61	60	70
				460-3-60	7.7	2	--	--	1-1/2	2.7	3/4	2.0	2	4.2	1	25	29	30	35
				208/230-3-60	16.0	2	--	--	2	7.0	3/4	4.3	2	10.6	1	52	63	60	70
460-3-60	7.7			2	--	--	2	3.5	3/4	2.0	2	4.2	1	26	30	30	35		
208/230-3-60	16.0			2	--	--	3	9.0	3/4	4.3	2	10.6	1	54	65	70	80		
460-3-60	7.7			2	--	--	3	4.3	3/4	2.0	2	4.2	1	27	31	30	35		
208/230-3-60	16.0			2	--	--	5	13.4	3/4	4.3	2	10.6	1	59	70	70	80		
460-3-60	7.7			2	--	--	5	6.6	3/4	2.0	2	4.2	1	29	33	35	40		
208/230-3-60	16.0			2	--	--	7-1/2	23.0	3/4	4.3	2	10.6	1	68	79	90	100		
460-3-60	7.7			2	--	--	7-1/2	9.7	3/4	2.0	2	4.2	1	32	36	40	45		
208/230-3-60	10 HP Blower motor is not available in these voltages.																		
460-3-60	7.7	2	--	--	10	13.0	3/4	2.0	2	4.2	1	35	40	45	50				
170	228	208/230-3-60	18.3	2	--	--	1	3.7	3/4	4.3	2	10.6	1	54	64	70	80		
		460-3-60	8.1	2	--	--	1	1.7	3/4	2.0	2	4.2	1	26	31	35	40		
		208/230-3-60	18.3	2	--	--	1-1/2	5.6	3/4	4.3	2	10.6	1	56	66	70	80		
		460-3-60	8.1	2	--	--	1-1/2	2.7	3/4	2.0	2	4.2	1	27	32	35	40		
		208/230-3-60	18.3	2	--	--	2	7.0	3/4	4.3	2	10.6	1	57	68	70	80		
		460-3-60	8.1	2	--	--	2	3.5	3/4	2.0	2	4.2	1	28	32	35	40		
		208/230-3-60	18.3	2	--	--	3	9.0	3/4	4.3	2	10.6	1	59	70	70	80		
		460-3-60	8.1	2	--	--	3	4.3	3/4	2.0	2	4.2	1	29	33	35	40		
		208/230-3-60	18.3	2	--	--	5	13.4	3/4	4.3	2	10.6	1	64	75	80	90		
		460-3-60	8.1	2	--	--	5	6.6	3/4	2.0	2	4.2	1	31	36	40	45		
		208/230-3-60	18.3	2	--	--	7-1/2	23.0	3/4	4.3	2	10.6	1	73	84	90	100		
		460-3-60	8.1	2	--	--	7-1/2	9.7	3/4	2.0	2	4.2	1	34	39	40	45		
208/230-3-60	10 HP Blower motor is not available in these voltages.																		
460-3-60	8.1	2	--	--	10	13.0	3/4	2.0	2	4.2	1	38	42	45	50				

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data

Engineering/Application Information (cont'd)

Electrical Data (cont'd)

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**	
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA
190	268	208/230-3-60	16.0	3	--	--	1	3.7	3/4	4.3	3	10.6	1	69	80	80	90
		460-3-60	7.7	3	--	--	1	1.7	3/4	2.0	3	4.2	1	34	38	40	45
		208/230-3-60	16.0	3	--	--	1-1/2	5.6	3/4	4.3	3	10.6	1	71	82	80	90
		460-3-60	7.7	3	--	--	1-1/2	2.7	3/4	2.0	3	4.2	1	35	39	40	45
		208/230-3-60	16.0	3	--	--	2	7.0	3/4	4.3	3	10.6	1	73	83	90	90
		460-3-60	7.7	3	--	--	2	3.5	3/4	2.0	3	4.2	1	36	40	40	45
		208/230-3-60	16.0	3	--	--	3	9.0	3/4	4.3	3	10.6	1	75	85	90	100
		460-3-60	7.7	3	--	--	3	4.3	3/4	2.0	3	4.2	1	37	41	40	45
		208/230-3-60	16.0	3	--	--	5	13.4	3/4	4.3	3	10.6	1	79	90	90	100
		460-3-60	7.7	3	--	--	5	6.6	3/4	2.0	3	4.2	1	39	43	45	50
		208/230-3-60	16.0	3	--	--	7-1/2	23.0	3/4	4.3	3	10.6	1	89	99	110	120
		460-3-60	7.7	3	--	--	7-1/2	9.7	3/4	2.0	3	4.2	1	42	46	50	50
208/230-3-60	10 HP Blower motor is not available in these voltages.																
460-3-60	7.7	3	--	--	10	13.0	3/4	2.0	3	4.2	1	45	50	50	50		
215	293	208/230-3-60	18.3	3	--	--	1	3.7	3/4	4.3	3	10.6	1	76	87	90	100
		460-3-60	8.1	3	--	--	1	1.7	3/4	2.0	3	4.2	1	38	42	45	50
		208/230-3-60	18.3	3	--	--	1-1/2	5.6	3/4	4.3	3	10.6	1	78	89	90	100
		460-3-60	8.1	3	--	--	1-1/2	2.7	3/4	2.0	3	4.2	1	39	43	45	50
		208/230-3-60	18.3	3	--	--	2	7.0	3/4	4.3	3	10.6	1	80	90	90	100
		460-3-60	8.1	3	--	--	2	3.5	3/4	2.0	3	4.2	1	39	44	45	50
		208/230-3-60	18.3	3	--	--	3	9.0	3/4	4.3	3	10.6	1	82	92	100	110
		460-3-60	8.1	3	--	--	3	4.3	3/4	2.0	3	4.2	1	40	44	45	50
		208/230-3-60	18.3	3	--	--	5	13.4	3/4	4.3	3	10.6	1	87	97	100	110
		460-3-60	8.1	3	--	--	5	6.6	3/4	2.0	3	4.2	1	43	47	50	50
		208/230-3-60	18.3	3	--	--	7-1/2	23.0	3/4	4.3	3	10.6	1	96	106	110	120
		460-3-60	8.1	3	--	--	7-1/2	9.7	3/4	2.0	3	4.2	1	46	50	50	60
208/230-3-60	10 HP Blower motor is not available in these voltages.																
460-3-60	8.1	3	--	--	10	13.0	3/4	2.0	3	4.2	1	49	53	50	60		
240	298	208/230-3-60	16.0	4	--	--	1	3.7	3/4	4.3	4	10.6	1	90	100	100	110
		460-3-60	7.7	4	--	--	1	1.7	3/4	2.0	4	4.2	1	44	48	50	50
		208/230-3-60	16.0	4	--	--	1-1/2	5.6	3/4	4.3	4	10.6	1	91	102	100	110
		460-3-60	7.7	4	--	--	1-1/2	2.7	3/4	2.0	4	4.2	1	45	49	50	50
		208/230-3-60	16.0	4	--	--	2	7.0	3/4	4.3	3	10.6	1	93	103	100	110
		460-3-60	7.7	4	--	--	2	3.5	3/4	2.0	3	4.2	1	46	50	50	50
		208/230-3-60	16.0	4	--	--	3	9.0	3/4	4.3	4	10.6	1	95	105	110	110
		460-3-60	7.7	4	--	--	3	4.3	3/4	2.0	4	4.2	1	47	51	50	50
		208/230-3-60	16.0	4	--	--	5	13.4	3/4	4.3	4	10.6	1	100	110	110	125
		460-3-60	7.7	4	--	--	5	6.6	3/4	2.0	4	4.2	1	49	53	50	60
		208/230-3-60	16.0	4	--	--	7-1/2	23.0	3/4	4.3	4	10.6	1	109	119	125	125
		460-3-60	7.7	4	--	--	7-1/2	9.7	3/4	2.0	3	4.2	1	52	56	60	60
208/230-3-60	10 HP Blower motor is not available in these voltages.																
460-3-60	7.7	4	--	--	10	13.0	3/4	2.0	3	4.2	1	55	60	60	60		

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data

Engineering/Application Information (cont'd)**Electrical Data (cont'd)**

Model PCCA Size	Model PCDA Size	Power	Cooling Compressors*				Blower Motor		Condenser Fan Motors			Dehumidifier Compressor		Minimum Circuit Ampacity		Maximum Fuse Size**	
			RLA	Qty	RLA	Qty	HP	FLA	HP	FLA	Qty	RLA	Qty	PCCA	PCDA	PCCA	PCDA
277	335	208/230-3-60	18.3	4	--	--	1	3.7	3/4	4.3	4	10.6	1	99	110	110	125
		460-3-60	8.1	4	--	--	1	1.7	3/4	2.0	4	4.2	1	49	53	50	60
		208/230-3-60	18.3	4	--	--	1-1/2	5.6	3/4	4.3	4	10.6	1	101	112	110	125
		460-3-60	8.1	4	--	--	1-1/2	2.7	3/4	2.0	4	4.2	1	50	54	50	60
		208/230-3-60	18.3	4	--	--	2	7.0	3/4	4.3	3	10.6	1	102	113	110	125
		460-3-60	8.1	4	--	--	2	3.5	3/4	2.0	3	4.2	1	51	55	60	60
		208/230-3-60	18.3	4	--	--	3	9.0	3/4	4.3	4	10.6	1	104	115	110	125
		460-3-60	8.1	4	--	--	3	4.3	3/4	2.0	4	4.2	1	51	56	60	60
		208/230-3-60	18.3	4	--	--	5	13.4	3/4	4.3	4	10.6	1	109	120	125	125
		460-3-60	8.1	4	--	--	5	6.6	3/4	2.0	4	4.2	1	54	58	60	60
		208/230-3-60	18.3	4	--	--	7-1/2	23.0	3/4	4.3	4	10.6	1	118	129	125	125
		460-3-60	8.1	4	--	--	7-1/2	9.7	3/4	2.0	3	4.2	1	57	61	60	70
		208/230-3-60	10 HP Blower motor is not available in these voltages.														
460-3-60	8.1	4	--	--	10	13.0	3/4	2.0	3	4.2	1	60	64	60	70		
360	438	208/230-3-60	16.0	6	--	--	1	3.7	3/4	4.3	4	14.4	1	122	136	150	150
		460-3-60	7.7	6	--	--	1	1.7	3/4	2.0	4	7.1	1	60	67	60	70
		208/230-3-60	16.0	6	--	--	1-1/2	5.6	3/4	4.3	4	14.4	1	123	138	150	150
		460-3-60	7.7	6	--	--	1-1/2	2.7	3/4	2.0	4	7.1	1	61	68	60	70
		208/230-3-60	16.0	6	--	--	2	7.0	3/4	4.3	4	14.4	1	125	139	150	150
		460-3-60	7.7	6	--	--	2	3.5	3/4	2.0	4	7.1	1	62	69	70	70
		208/230-3-60	16.0	6	--	--	3	9.0	3/4	4.3	4	14.4	1	127	141	150	150
		460-3-60	7.7	6	--	--	3	4.3	3/4	2.0	4	7.1	1	63	70	70	70
		208/230-3-60	16.0	6	--	--	5	13.4	3/4	4.3	4	14.4	1	132	146	150	150
		460-3-60	7.7	6	--	--	5	6.6	3/4	2.0	4	7.1	1	65	72	70	80
		208/230-3-60	16.0	6	--	--	7-1/2	23.0	3/4	4.3	4	14.4	1	141	155	150	175
		460-3-60	7.7	6	--	--	7-1/2	9.7	3/4	2.0	4	7.1	1	68	75	70	80
		208/230-3-60	10 HP Blower motor is not available in these voltages.														
460-3-60	7.7	6	--	--	10	13.0	3/4	2.0	4	7.1	1	71	78	80	80		

* Combinations of compressors are used across the product line. Each individual compressor has nominal capacity ratings of 5 or 6-1/4 tons.

** Maximum Fuse Size - Maximum Time Delay Fuse or HACR Circuit Breaker

Please contact factory to verify critical data